

Armstrong Ag

RR-Rodent Ridder

For underground placement of treated bait for gophers. The Armstrong Ag RR (Rodent Ridder) uses a 17" coultter to slice through the root & grass mat. This minimizes ground disturbances by the shank. The drop tube is attached, directly to the hopper; which eliminates spillage. Also the hopper is attached directly to the shank & has a spill proof lid. The drive/packer wheel has a unique design allowing for better traction & lessens tunnel collapses.



Operation:

After tractor hookup, raise unit, remove & place stands in operation position. Lower unit & level frame. Read bait manufactures' application & safety recommendations.

Use great care when handling. **THIS IS POISON!!!**

Make sure hopper, drop tube, & shank are clean & assure that bait drops freely before filling hopper. Secure lid.

ALWAYS RAISE UNIT WHEN MAKING TURNS!!!

To eliminate bait drops above ground; stop travel before raising. This will lessen drive wheel spinning.

When finished the hopper should be emptied & bait stored in a secure place.

Before storing, grease all zerks & apply light oil inside hopper on seed metering shaft. Solid drive wheel optional.

APPLICATION INSTRUCTIONS:

This unit has a seed meter with two application settings. It is shipped from the factory with the one hole setting. Driving 25' apart will place approx. 2 lbs. per acre.

Reversing seed meter to two hole setting will double this rate.

